



AUTOMATIC MINCERS

PA-130

PA-160

PA-200

GENERAL CHARACTERISTICS:

- The automatic mincers Castellvall present the best quality results in products. They are designed for the most varied needs of trade and industry.
- PA-130 is an automatic mincer at angle feeding with two feed-screws: the cross feed and the cutting ones are crucial in feeding and chopping the fresh meat without slicing the pieces and avoid heating up the meat.
- Its technology development, combined with the finest materials and excellent finishing, guarantee optimal working results in each phase.
- Heavy duty construction made of AISI-304 stainless steel.
- Machine made according to the European Directive 2006/42/CE.
- Very silent operation and maintenance-free.
- Safety mechanisms with emergency STOP.
- Switch gear cabinet and control panel at 24V IP65.
- Its height allows the manual loading of the hopper. For dumping in 100l. carts. (*Only PA-130*)
- Supplied with 1 speed / gear and, optionally, with 2 speeds / gears.
- Supplied with 1 set of plates and knives, complete with all the accessories.



INDUSTRIES CASTELLVALL 2002, S.L.

Pol. Ind. Girona – Avda. Països Catalans, 162-164
17457 RIUDELLOTS DE LA SELVA (Girona - ESPAÑA)
Phone: +34 972 478 399 Fax +34 972 477 594
Castellvall@castellvall.com

WWW.CASTELLVALL.COM

OPTIONS:

	PA-130	PA-160	PA-200
Supplement for 225-liter Hopper raised machine for download 200 liter cutter carts.	✓	-	-
2 speeds motor suitable for guillotined above product at -12°C.	✓	✓	✓
Endless screw step: short (standard) or super long (special).	✓	✓	✓
Column elevator for 200-liter cutter carts attached to machine.	✓	✓	✓

PRODUCTION GUIDANCE:

Speed	Plate	Meat temperature	Production (Output)		
			PA-130	PA-160	PA-200
1 ^a	Ø 6 mm.	0°C	1500 Kg/h.	3000 Kg/h.	6000 Kg/h.
1 ^a	Ø 3 mm.	0°C	900 Kg/h.	1200 Kg/h.	3500 Kg/h.
2 ^a	Ø 6 mm.	0°C	1800 Kg/h.	5000 Kg/h.	8500 Kg/h.
2 ^a	Ø 3 mm.	-12°C	1200 Kg/h.	3000 Kg/h.	5500 Kg/h.

TECHNICAL DATA:

	PA-130	PA-160	PA-200
Outlet diameter	130 mm.	160 mm.	200 mm.
Hopper capacity	140 liters / 225 liters	225 liters	340 liters
Motor power	9,2 kw (with 2 speeds 6,5/11 kw)	22 kw (with 2 speeds 25/30 kw)	37 kw (with 2 speeds 30/45 kw)
Dimensions (AxBxH) mm.	1450x1090x1335	1480x1345x1645	1665x1604x1650
Weight	505 kg.	820 kg.	1010 kg.

