

GENERAL CHARACTERISTICS:

- Heavy duty construction made of AISI-304 stainless steel.
- Machine made according to the European Directive 2006/42/CE.
- Meat feeding system by rotor of 7 or 14 paddles.
- Vacuum group protected by condensing filter with pump stop security mechanism.
- The height and position of the knee switch can be adjustable.
- Independent and variable supply propeller speed.
- Easy extraction of the feeding system and the rotor for cleaning.
- Charger of cutter carts of 200 liter included.
- Can be connected to hamburger formers, meatballs formers and automatic clippers, etc.
- Supplied with the following standard accessories:
1 set of 3 funnels (12 mm. conic, 20 mm. and 30 mm.) 1 tools set, 2 spare paddles and 1 user's handbook.



OPTIONS:

- Twister adaptation.
- Twister (supplied with all the accessories, 1 set of 3 funnels of 12, 15 and 18 mm)
- Automatic twist linker for natural and artificial casings.
- Elevator with front loader.
- Meatballs and croquettes former.
- Hamburger former.
- Casing feeder with support and filters.
- Mincing head and minced meat portioner

TECHNICAL DATA:

Servo motor power	22,5 N.m.
Vacuum pump	0,75 Kw, 21 m ³ /h
Portions weight	10 – 100.000 grammes
Maximum production	1.200 portions/minute
Accuracy	Exactly
Free outlet production	6000 Kg/h, 60 mm Ø max.
Stuffer max. Pressure	45 Bar.
Weight (Kg)	860 Kg.
Hopper capacity	250 liter
Stuffer dimensions (AxBxH) (mm)	1.950x1.355x1.890 mm (max. height)

